



Oxygen Single Gas Detector BW Clip, operating period 24 months from activation

Order number: AS-04078

The oxygen single-gas detector BW Clip is an everyday companion for hazardous environments. It operates 24 months maintenance-free. Just turn on the device and it runs continuously. No need for calibration, sensor replacement, battery replacement or battery charging. That means great reliability and no downtime.

- low acquisition and operating costs
- 24 months continuously operating time from activation
- maintenance-free, no sensor or battery replacement
- compact, light design with one button control
- designed for a range of harsh environments and extreme temperatures
- automated self-test of battery, sensor and electronics every 24 h
- optical, acoustic (95 dB) and haptic signal
- automatic logging of the 35 most recent gas events and bump test results
- waterproof
- fixing with crocodile clip

dimensions: 4.1 x 5.0 x 8.7 cm

Display: 3,4 inch

default low alarm level: 19.5 %

default high alarm level: 23.5 %

temperature range: -20 – +50°C

ingress protection: IP 66/67

weight: 92 g

approvals: class I, Div. 1, Gr. A, B, C, D class I, Zone 0, Gr. IIC
Ex II 1G ATEX: Ex ia IIC T4, DEMKO 14 ATEX 1356 IECEx: Ex ia
IIC T4, IECEx UL 14.0063 CE