



Multi-Gas Detector GasAlertMax XT II, simple operation, with SmartSample pump

Order number: AS-04080

Simple operation with SmartSample pump. GasAlertMax XT II reliably monitors up to four hazards and combines straightforward one-button operation with our robust, motorised pump for intelligent, remote sampling, ideal for confined spaces.

- minimal costs and training thanks to one-button operation
- continuous LCD shows real-time gas concentrations
- compact and lightweight design makes it comfortable to wear
- simple automatic calibration procedure
- full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- optical, acoustic (95 dB) and haptic signal
- built-in concussion-proof boot
- integrated sampling pump with reliable diaphragm technology
- best in class block detection with semi-conductor pressure sensor
- multi-language support in English, French, German, Spanish and Portuguese
- equipped with standard data logging and event logging
- alarm levels for all sensors are user adjustable
- fixing with crocodile clip
- waterproof

supplied with:

3 m gas sampling hose with adapter
Li-Polymer-battery, integral
230 V recharger cable

dimensions: 13.1 x 7.0 x 5.2 cm

measuring range H2S: 0-200 ppm

measuring range CO: 0-1000 ppm

measuring range O2: 0-30 %

measuring range combustible gases: 0-100 % LEL / 0-5 Vol. %

temperature range: -20 – +50 °C

ingress protection: IP 66/67



battery operation time: 13 h at 0 °C
recharging time: approx. 6 h
weight: 328 g

approvals: EMV/RFI: complies with EMC directive 2004/108/EG
Class I, Div. 1, Gr. A, B, C, D IECEx: Ga Ex ia IIC T4 ATEX: CE
Ex II 1 G Ga Ex ia IIC T4 Br Ex ia IIC T4