



Multi-Gas Detector GasAlertQuattro, visual auditing, easy compliance

Order number: AS-04085

Rugged and reliable, the GasAlertQuattro four-gas detector combines a comprehensive range of features with simple one-button operation. With flexible power options, the GasAlertQuattro is always ready. The graphic LCD displays easy to identify icons that indicate operational information, such as bump test and calibration status for simplified onsite auditing. IntelliFlash provides continuous visual confirmation of detector operation and compliance. Suited to a wide range of industrial applications including confined space entry.

- continuous LCD shows real-time gas concentrations
- compact and lightweight design makes it comfortable to wear
- simple automatic calibration procedure
- full function self-test of sensors, battery status, circuit integrity and audible/visual alarms on start up and continuous testing on sensors
- optical, acoustic (95 dB) and haptic signal
- built-in concussion-proof boot
- powered by an interchangeable rechargeable battery pack or alkaline pack with 3 AA batteries
- one-button operation and straightforward user interface minimizes training
- comprehensive data logging and event logging capacity
- IntelliFlash verifies operation and compliance to both the user and supervisors from up to 6.1 m
- enhanced resistance to common industrial cross sensitive gases such as methanol and ethanol (CO and H2S sensors)
- multi-language support in English, French, German, Spanish and Portuguese
- field-proven SureCell sensors offer an unprecedented performance in even the harshest environments.
- alarm levels for all sensors are user adjustable
- fixing with crocodile clip

supplied with:

Li-Polymer-battery, changeable

dimensions: 13.0 x 8.1 x 4.7 cm

measuring range H2S: 0-200 ppm



measuring range CO: 0-1000 ppm
measuring range O2: 0-30 %
measuring range combustible gases: 0-100 % LEL / 0-5 Vol. %
temperature range: -20 - +50 °C
ingress protection: IP 66/67
battery operation time: 14 h
rechargeable battery operation time: 18-20 h
weight: 316 g (with rechargeable battery), 338 g (with Alkaline-battery pack)

approvals: EMV/RFI: complies with EMC directive 2004/108/EC
Class I, Div. 1, Gr. A, B, C, D IECEx: Ga Ex ia IIC T4 ATEX: CE
Ex II 1 G Ga Ex ia IIC T4 Br Ex ia IIC T4