



PETZL VOLT Harness

Order number: HR-02355

Fall arrest and work positioning harness with attachment point for vertical progression on rail or cable

The fall arrest and work positioning VOLT harness is very easy to don, thanks to the FAST LT PLUS and FAST LT automatic buckles that allow it to be donned with feet on the ground. Wide, semi-rigid waistbelt and leg loops give excellent support. Its lightweight, breathable construction maximizes air flow. It is certified to European and Russian standards.

- the self-locking DOUBLEBACK buckles on the hip belt and shoulder straps allow for precise adjustment
- the position of the foam padding of the leg loops can be adjusted to ensure an optimal fit
- the semi-rigid, wide hip belt and semi-rigid, wide leg loops ensure optimal support
- the ergonomic shape of the foam-padded shoulder straps reduces friction points on the neck or throat. when the hip belt is loaded, the load is transferred to the shoulder straps and distributed to the shoulders
- the LADDER CLIMB climbing protection eyelet is suitable for all purposes (ascending, work positioning and short-term free-hanging work) and allows a lanyard, a descender or a fall protection runner to be attached. When moving vertically on a rail- or wire-guided system, the LADDER CLIMB climbing protection eyelet allows the runner to be attached in a ventral position, distributing the load on the hip belt and ensuring optimum comfort. In the event of a fall, the climbing protection eyelet automatically moves to the sternal position to ensure an upright posture after the fall
- retractable lateral retaining eyelets prevent hanging when not in use.
- stowage system on each shoulder beam for the MGO lanyard connectors for fall protection. In the event of a fall, this system allows the fall arrest lanyard to be ripped open by releasing the MGO lanyards.
- material loops, fastening options for CARITOOL tool holder and TOOLBAG tool bag facilitate sorting of work tools

Specifications

- ventral LADDER CLIMB fall arrest eyelet: for attaching a



lanyard for work positioning, a descender or a fall arrest runner

- lateral retaining eyes: for attaching a lanyard for work positioning
- stern fall arrest eyelet: for attaching the fall arrest system
- rear fall-arrest eyelet: for attaching the fall-arrest system
- attachment eyelet on the back of the waist belt: for attaching a lanyard for restraint

material(s): nylon, polyester, aluminum, steel

size 0:

waist belt: 65-80 cm

leg loops: 44-59 cm

stature: 160-180 cm

weight: 2.1 kg

size 1:

waist belt: 70-93 cm

leg loops: 47-62 cm

stature: 165-185 cm

weight: 2.15 kg

size 2:

waist belt: 83-120 cm

leg loops: 50-65 cm

stature: 175-200 cm

weight: 2.23 kg

CE EN 361, CE EN 358, CE EN 813, EAC