



PETZL ASAP, mobile Fall Arrest Device for Rope

Order number: HR-03010

With its unique locking system, the ASAP sets the standard in fall protection for workers at height. In normal use, the device moves freely along the rope without any manual intervention and follows the user in all his/her movements. In case of shock or sudden acceleration, the ASAP locks on the rope and stops the user. Depending on use, the ASAP may also be combined with an ASAP'SORBER or ASAP'SORBER AXESS energy absorber to work at a distance from the rope.

- blocks in case of falls, slips and uncontrolled rappels
- works on vertical or inclined ropes
- locks on the rope even if the user reaches for the device during the fall
- slides up and down the rope without manual intervention
- can be easily attached and detached anywhere on the rope
- the fall arrester enables the use of the device when rescuing two persons with a load of up to 250 kg
- certified according to European and Russian standards when used with an OK TRIACT-LOCK carabiner
- certified according to American standards when used with a Bm'D or OXAN TRIACT-LOCK carabiner (international version)

Specifications

material(s): aluminum, stainless steel

weight: 295 g

CE EN 12841 type A when used with an OK TRIACT-LOCK carabiner and an EN 1891 type A, 10-13 mm rope. An ASAP'SORBER or ASAP'SORBER AXESS energy absorber can be used when needed

CE EN 353-2 when used with an OK TRIACT-LOCK carabiner and an ASAP'AXIS 11 mm rope. An ASAP'SORBER or ASAP'SORBER AXESS energy absorber can be used when needed

EAC when used with an OK TRIACT-LOCK carabiner and an EN 1891 type A, 10-13 mm rope. An ASAP'SORBER or ASAP'SORBER AXESS energy absorber can be used when needed



ANSI Z359.15 when used with an ASAP'SORBER or ASAP'SORBER AXESS energy absorber, a Bm'D or OXAN TRIACT-LOCK (international version) carabiner, a CAPTIV positioning bar, and a RAY 12 mm rope