



## PETZL RIG Descender

**Order number:** HR-03020

RIG is a compact self-braking descender for rope access, designed for experienced users. It has an ergonomic handle that allows comfortable descent control. The AUTO-LOCK system allows users to easily position themselves at the work station without having to manipulate the handle or tie off the device. Once locked, the rope can be taken up without having to manipulate the handle. The safety gate allows the rope to be installed with the device remaining connected to the harness.

- designed for experienced users in difficult access conditions
- the movable side part is equipped with a safety clip so that the device can easily remain hooked to the harness when inserting the rope to facilitate the passing of intermediate belays
- Guide groove and markings simplify rope insertion
- the ergonomically designed lever can be used to release the rope and control the descent comfortably. Two abseiling modes: on the side panel or in the V-shaped brake groove
- when the rope is removed from the device, the lever automatically goes to the "park" position to reduce the risk of snagging the descender worn on the harness
- the operation of the clamping cam allows the delivery of rope or belaying in the lead
- stainless steel reinforcement that protects the device from rope friction and increases wear resistance
- abseiling of heavy loads up to 200 kg
- Rope compatibility: 10 to 11.5 mm diameter

### Specifications

material(s): aluminum, steel, nylon

weight: 400 g

max. working load: 200 kg

EN 341 type 2 class A, CE EN 12841 type C, CE EN 15151-1, NFPA 1983 Technical Use, EAC - EN 341 type 2 class A when used with PARALLEL 10.5 mm or AXIS 11 mm rope - EN 12841 type C when used with a 10 to 11.5 mm EN 1891 A rope - EN 15151-1 when used with a 9 to 11 mm rope - NFPA 1983 Technical Use when used with a 10 to 11.5 mm rope