



## AWG Turbo-Nozzle 2400 Gold, Storz C-coupling, DIN EN 15182, 130/235/400 l/min

**Order number:** LT-01005

The AWG Turbo Nozzle Gold allows intuitive working even in difficult and stressful situations. With well manageable, effective features, you can focus on firefighting. New materials also reduce the weight and protect the AWG Turbo Nozzle Gold against shock and corrosion.

On the rotating ring, you can easily select the flow rate: 130, 235 or 400 l / min (6 bar). Even in poor visibility, you have the setting under control: A distinctive button (pointer) shows you the selected value. When changing the rotary ring engages audibly and clearly noticeable. Dirt particles up to a diameter of six millimeters can be easily rinsed out.

The high quality anodized surface of the Turbo Nozzle Gold is even more corrosion resistant thanks to a special after treatment. In the salt spray test in accordance with DIN EN ISO 9227-NSS it is much more resistant than conventional anodizing. This nozzle with the new anodized finish is a lightweight alternative to brass or gunmetal. Shifter and handle made of impact-resistant polyamide also allow the arm and shoulder muscles to breathe.

dimensions: 300 x 112 x 245 mm

inlet: 52-C

flow rate selection: 130/235/400 l/min

pressure: 6 bar

weight: 2,4 kg

DIN EN 15182