

AWG Turbo-Nozzle 2400 without handle, Storz C-coupling, DIN EN 15182, 130/235/400 l/min

Order number: LT-01027

AWG-Turbo-Nozzles meet the standard DIN EN 15182-1 for branchpipes. The flow rates can be selected by the adjusting sleeve, and opening and closing by means of the lever. A special feature is the extinguishing power, due to optimal droplet size also at the full range of the 0° to 120° adjustable water-filled spray stream. The AWG-Nozzles have two pointers, a good aid to feel the selected flow rate as well as the type of the stream. With Flash-Over position.
Inlet also swiveling under pressure.

dimensions: 290 x 109 x 245 mm
inlet: 52-C
flow rate selection: 130/235/400 l/min
pressure: 6 bar
range of jet effective solid jet: 26-32-40 m
range of jet effective water spray: 11-14-16 m
spray angle max: 120°
weight: 2.4 kg

DIN EN 15182-1

rescue-tec Gmbh & Co. KG
Oberau 4-8
65594 Runkel-Ennerich, Deutschland

E-Mail info@rescue-tec.de
Tel.: +49-6482-608900
Fax.: +49-6482-608920

• **schnell** im Service
• **kompetent** in der Beratung
• **zuverlässig** in der Abwicklung