

Wildfire Hose TITAN FLAME, D25, 30 m, DIN 14811, STORZ coupling and protective collar

Order number: LT-02053

• self-humidifying through perforation
• no fountain formation even at >60 bar
• very small bending radius, therefore fewer kinks and longer life time
• extremely high abrasion resistance thanks to the special G&H 4Z system
• more than 100 bar burst pressure for large performance reserves
• distinctive design for high visibility through contrast weaving
• standard protective sleeve G&H HOSE-GUARD against defects in the coupling area
• corrosion-resistant hose cover made of stainless steel wire
• minimized tendency to twist and stretch
• suitable for all types of hose washing systems
• inner rubber made of high quality EPDM rubber, flexible at low temperatures, also suitable for hot water

material: polyester
operating pressure: 30 bar
burst pressure: 100 bar
bending radius: 300 mm
water loss: 2 l / min at 6 bar operating pressure (tested on 100 m hose line)

colour: neon orange with yellow stripes

DIN 14811 - class 1

rescue-tec Gmbh & Co. KG
Oberau 4-8
65594 Runkel-Ennerich, Deutschland

E-Mail info@rescue-tec.de
Tel.: +49-6482-608900
Fax.: +49-6482-608920

• **schnell** im Service
• **kompetent** in der Beratung
• **zuverlässig** in der Abwicklung