



AWG Siamese with 3 Inlets and 1 Outlet A3B, with non return flaps and ventilation valves

Order number: LT-03110

During extinguishing operation of fire fighters, the water pipelines could be contaminated and with it the drinking water. Possible causes are faulty operation of equipment or power drop of the mains supply. Admixing of foam agents is a particular hazard of the drinking water. In addition water hammer pressure by tank filling armatures or vacuum in the water pipelines due to different performance of fire pump and drinking water network, can damage the drinking water pipelines and contaminate the drinking water. AWG safety devices in standpipes, siameses, dividers and check valves avoid a backpressure, resuction or reflow of firefighting water into the drinking water network. The built-in clappers and check valves close automatically as soon as a water hammer will arrive. Two integrated aerators in the Storz 75-B adapter work fully automatic. At the smallest vacuum in the fire network, air will stream from outside and avoid vacuum in the fire water pipelines. In compliance with the technical rules (06/2015) of DVGW – bulletin E-W405 – B1 and W 408. Use of reverse flow preventer type EA acc. to DIN EN 1717

The three-way drinking water security siamese is equipped with three single non-return flaps. In each adapter at the siamese inlet, two ventilation valves are integrated.

dimensions: 273 x 373 x 182 mm

Inlet: 3 x 75-B

Outlet: 110-A

weight: 7.5 kg