



## Setolite LED Spotlight Aldebaran Raptor R, for DeWalt, Makita and Milwaukee batteries

**Order number:** TH-04224

The cordless floodlight Raptor R can be operated with the system batteries of the well-known manufacturers and therefore offers maximum flexibility and speed on site. The Xpect LED module with pre-focused lenses delivers a homogeneous luminous flux of 10.000 lumens and is therefore subjectively even brighter than a classic 1.000 W halogen spotlight.

### The Raptor R can do more

It is operated via two large pushbuttons on the back. The Raptor R can be dimmed to 50% or 25% for a longer runtime. In addition, the spotlight also offers three different flashing modes (flashing, double flash). The Raptor R can also be used as a signal light together with the supplied blue and orange cover plates.

### Universal for your existing system

Most vehicles already have a large number of cordless tools. No matter which system you have already decided on, the Raptor R integrates seamlessly. It is available with two different battery removable plates for the 18 V system batteries of the common manufacturers:

MBHP = Makita, Bosch, Hitachi, Panasonic

DMM = Dewalt, Metabo, Milwaukee

You don't have to buy a new system for the Raptor R and you don't have to manage any additional battery management.

### Ready for the future

The Raptor R replaces the 1,000 W halogen spotlight in terms of dimensions, weight and light output and offers the well-known advantages of LED technology in terms of service life, heat generation, efficiency and light color. Thanks to the battery technology, you are more flexible and faster than ever before. Insert the battery, illuminate the place of use, without compromise.

### Details for the professionals

Rubber corners as additional shock protection, holder for the additional panes, comfort carrying handle, robust support foot made of 5 mm thick aluminum, multi-stage tilt adjustment mechanism, housing made of aluminum and V2A stainless steel, passive cooling, receptacle for standard spigot DIN 14640, neutral white light color, 230 V connection Via a separately available power supply unit - The Raptor R has been consistently developed for professional use.

- operation with 18 V system batteries from all common manufacturers
- compact and robust
- support for standard spigot according to DIN 14640
- with stand
- particularly homogeneous light distribution based on the halogen spotlight
- glare-free light without scattering losses thanks to SETO Xpect lens technology

supplied with:

2 front panels (1x orange and blue each)

input voltage: 18 V

color temperature: 4.000 K

CRI:> 70

light source: Xpect LED module

lifespan: 50,000 h

ambient temperature: -40 ° C to +50 ° C

degree of protection: IP54

mains connection: via a separately available power supply unit

running time: approx. 2 hours at 100% with an 8 Ah battery

weight: 4.7 kg