28.03.2024 1 von 2





Fire Brigade Suction Pump Hero FPS, flow rate 230 l/min, container volume 45 l

Order number: TH-05010

This modern professional suction pump is specially designed for fire brigades. With the Hero FPS you are prepared for continuous use in floods and high water of all kinds. Contaminated wastewater, sludge, rocks and other non-flammable liquids can be absorbed efficiently. Thanks to its particularly compact design, it is easy to load on vehicles and can also be used in confined spaces.

The focus is clearly on highest safety and performance. The Hero FPS comes as standard with a 10-meter connection cable (H07RN-F) with pressure-water-tight plug with integrated PRCD personal safety switch.

The impact-resistant and compact plastic container allows optimum mobility with a low total weight of only 19 kg. Many equipment features, such as the separately switchable pump, large wheels made of solid rubber with parking brake and the Storz C-coupling guarantee reliability with every use.

- accessories can be conveniently stowed away at the teat
- Storz C coupling for the pumping hose
- large wheels with parking brake for high mobility
- overflow protection
- robust and impact-resistant plastic
- integrated personal protection switch
- completely drained via drain hose
- numerous reflective strips for more safety

supplied with:

2 stainless steel suction pipes, 50 cm

1 metal floor nozzle, 45 cm

1 crevice nozzle

1 filter net

1 suction hose, 7 m

1 dirty water hose, 10 m

power consumption: 2200 W intake capacity: 150 I / min flow rate pump: 230 I / min

E-Mail info@rescue-tec.de
Tel.: +49-6482-608900 • kom
Fax.: +49-6482-608920 • zuverli

schnell im Service
 kompetent in der Beratung
 zuverlässig in der Abwicklung

×

flow rate: max. 70 l/s

negative pressure: max. 230 mbar

connection cable: 10 m H07RN-F3x15 with Schuko plug IP68

container volume: max. 45 l gross

suction height: full suction max. 2,3 m, snare mode max. 5-8

m

delivery height from vacuum: max. 9 m

delivery width: max. 50 m grain passage: 34 mm

E-Mail info@rescue-tec.de

+49-6482-608900

+49-6482-608920

Tel.:

Fax.:

dimensions (WxHxD): 44 x 93 x 50 cm

weight: 19 kg