



ADALIT LED Hand Lamp L-3000 Power, max. 300 lm, rechargeable, ATEX

Order number: TL-03009

The new L-3000 Power has an improved power-optics with in total three high performance LED which generate in combination 300 Im luminous flux. It fulfils all requirements on a professional safety hand lamp for fire service, military and industry applications. The swivelling head makes this torch universally applicable, regardless of whether as hand lamp or adapted on a holster.

- lithium ion battery easy exchangeable by the user
- digital display of remaining light on swiveling head in minutes and hours
- alert signal/blinking signal when battery power is low in the last 15 minutes
- self-checking mode (maintenance) and mode for charging time/discharging time available
- suitable for all ADALIT chargers placed on the market
- swiveling head by 0°/45°/90°
- housing made from antistatic thermoplastic, especially resistant to chemicals, extreme temperature and mechanical load
- new revolutionary optical sensor unit makes perfect illumination possible concerning field of view by means of two LEDs
- various light settings, both LEDs light up at the same time (focused power light ray and scattered light), blinking light (adjustable in 5 frequencies), scattered light with focused power light ray
- operating time of both LEDs (2 x 3 watt LEDs = 200 lumen) programmable from 4 hours to 6 hours or 8 hours
- easy operation with gloves by new ergonomic push-button switch
- protection class IP67, dust-proof and water-proof
- highest protection class for operation in zone 0 + 1 + 2 and 20 + 21 + 22

dimensions: 22.5 x Ø 7 cm

E-Mail info@rescue-tec.de

+49-6482-608900

+49-6482-608920

lamp: LED

Fax.:

luminance: 135 lumen per LED, max. 200 lm

×

lumination time: 4, 6 or 8 hours (depending on active modes)

luminous ramge: 245 m

E-Mail info@rescue-tec.de

+49-6482-608900

+49-6482-608920

Tel.:

Fax.:

waterproof: IP67

batteries: lithium ion 3.7 V 4 Ah, rechargeable

weight: 500 g

EX II 1G Ex ia IIC T4 Ga eX II 1D Ex ia IIIC T85 °C Da

DIN 14649