

WRS rescue board MEGA SLED, for up to 10 persons

Order number: WR-06000

Rescue board for up to 6 people in fast-flowing water and with the tailgate open. When the tailgate is closed, the capacity is around 8–10

people (1.000 kg).

High Volume Sponson Tubes

With a raised bow height the sled is able to handle swift water tethers and rescues reducing the risk of the bow diving when loaded with a rescuers or causality. The high volume sled maximises stability and confidence.

Inflation and over pressure valves

Leafield valves are used and are widely recognised as world leaders in valve manufacturing. Our valves all work with boat inflation kits.

Low profile grab handles

Fitted with 6 low profile grab handles, aiding team carries and in-water casualty management.

1000kg (10KN) breaking load D rings attachments

6" Airdeck hull

Using the knowledge in stand up paddle board manufacturing WRS can offer inflatable hulls that match that superb shape, stiffness and form.

3 Chambers

The sled is built with 3 separate inflatable chambers, providing added security should one of the chamber become compromised.

Reinforced hull

An additional fabric strake is added to the hull to increase durability in service.

Transom Flap

Converting the Sled from open back self bailing craft to a sealed dry deck area for transportation of flood victims were staying dry is preferable.

E-Mail info@rescue-tec.de Tel.: +49-6482-608900 Fax.: +49-6482-608920



6 Person craft

The sled has been designed to carry 6 occupants happy in swift water with the Transom Flap down. When Transom Flap is in use the capacity is 1000kg approx 8-10 people. (Note the when Transom Flap is used the craft is no longer self bailing)

Comes complete with Standard Bag

floor thickness: 15 cm tube width: 50 cm capacity: 600 kg with the tailgate open, 1.000 kg with the tailgate closed

material: PVC Fusion dropstitch material D-rings: stainless steel length: 3.63 m width: 1.80 m pack size: 120 x 60 x 35 cm weight: 32 kg

E-Mail info@rescue-tec.de Tel.: +49-6482-608900 Fax.: +49-6482-608920 schnell im Service
kompetent in der Beratung
zuverlässig in der Abwicklung

×