30.04.2024 1 von 2





# WRS rescue board X-SLED, for 3 persons

Order number: WR-06010

The X-Sled has been designed to carry 2 rescuers and 1 casualty. Although the sled will float up-to 5 people successfully this does affect its use in turbulent water.

# **High Volume Bow and Rocker**

With a raised bow height the X-Sled is able to handle tethers in swift water whilst reducing the risk of the bow diving when loaded. The increased volume maintains stability when occupied by a casualty or rescuer.

### Inflation and over pressure valves

Leafield valves are used and are widely recognised as world leaders in valve manufacturing. Our valves all work with boat inflation kits.

# Low profile grab handles

Fitted with 15 low profile grab handles, aiding team carries and in-water casualty management.

#### 6" Airdeck hull

Using our factories world leading knowledge in stand up paddle board manufacturing we can offer inflatable hulls that match that superb shape, stiffness and form.

#### 3 Chambers

The sled is built with 3 separate inflatable chambers, providing added security should one of the chamber become compromised.

Double Layer Drop Stitch Fabric Hull using new Fusion Technology to create a light strong platform

Comes complete with Pro Bag

floor thickness: 15 cm tube width: 24 cm

capacity: 600 kg with the tailgate open, 1.000 kg with the

tailgate closed

material: PVC Fusion dropstitch

E-Mail info@rescue-tec.de Tel.: +49-6482-608900 Fax.: +49-6482-608920

×

material D-rings: stainless steel

length: 3.55 m width: 1.22 m

pack size: 95 x 50 x 28 cm

E-Mail info@rescue-tec.de

Tel.:

Fax.:

+49-6482-608900

+49-6482-608920

weight: 20 kg