

HAIX Black Eagle Safety 40.1 MID, S3 safety shoes, black-silver

Order number: WW-01450

Upper Material
Microfibre/textile combination

Inner Lining
GORE-TEX Extended; 3-layer GORE-TEX laminate, waterproof and highly breathable. Abrasion-resistant lining with optimized climate comfort, especially for flexible alternating inside and outside use

Insert
comfortable, cushioning, moisture repellent, anti-bacterial. Separate heel shape for good cushioning and foot insertion. "AIRFLOW" channels. "Perfect-Fit" mark for an optimal verification of the correct shoe size

Anti Slip
very good grip on different terrains by profile configuration and use of a special rubber

Protective Throughsole
flexible, lightweight and metal-free sole insert

Sole
modern, light weight and sporty sole construction with rubber/PU street/terrain tread, abrasion-proof, for enhanced toe-to-heel support, ideal for cold weather conditions. The lightweight PU cushioning wedge provides optimum wear comfort. Excellent thermal insulation. The nonmarking outer sole is resistant to heat, oil and gasoline

ESD
electrostatically conductive footwear tested according to DIN EN 61340-4-3:2002

HAIX Composite Toe Cap
anatomically formed and ultralight protective toe cap made of fiber-reinforced plastic for highest safety requirements

HAIX Climate System
HAIX Climate System with Micro-Dry lining along the upper

rescue-tec Gmbh & Co. KG
Oberau 4-8
65594 Runkel-Ennerich, Deutschland

E-Mail info@rescue-tec.de
Tel.: +49-6482-608900
Fax.: +49-6482-608920

• **schnell** im Service
• **kompetent** in der Beratung
• **zuverlässig** in der Abwicklung

edge of the shaft

HAIX Vario Wide Fit System
choose from 3 different inserts to adjust the boot to the width of your foot

Others
low weight, antistatic, metal-free, leg height 12 cm, antistatic

CE EN ISO 20345:2011 S3 HRO HI CI WR SRC

sizes: UK 3–15 / EU 35–51
outsize extra charge: size UK 12.5–15 / EU 48–51

rescue-tec Gmbh & Co. KG
Oberau 4-8
65594 Runkel-Ennerich, Deutschland

E-Mail info@rescue-tec.de
Tel.: +49-6482-608900
Fax.: +49-6482-608920

• **schnell** im Service
• **kompetent** in der Beratung
• **zuverlässig** in der Abwicklung