25.04.2024 1 von 2





HAIX Black Eagle Safety 56 LOW, S3 safety shoes

Order number: WW-01496

Upper Material

Waterproof Leather, hydrophobic, breathable, 2.0 - 2.2 mm thick

Inner Lining

Breathable inner liner

Insert

Comfortable, cushioning, moisture repellent, anti-bacterial. Separate heel shape for good cushioning and foot insertion. "AIRFLOW" channels. "Perfect-Fit" mark for an optimal verification of the correct shoe size.

Sole

Modern, light weight and sporty sole construction with rubber/PU street/terrain tread, abrasion-proof, for enhanced toe-to-heel support, ideal for cold weather conditions. The lightweight PU cushioning wedge provides optimum wear comfort. Excellent thermal insulation. The non-marking outer sole is resistant to heat, oil and gasoline.

Anti Slip

Very good grip on different terrains by profile configuration and use of a special rubber.

Protective Throughsole

Flexible, lightweight and metal-free sole.

HAIX Composite Toe Cap

Anatomically formed and ultralight protective toe cap made of fiber-reinforced plastic for highest safety requirements.

HAIX Climate System

The HAIX Climate system uses the pumping movement, which permits air circulation with every step - warm air is released through the Micro-Dry lining at the top of the boot leg.

ESD

Fax.:

Electrostatically conductive footwear tested according to DIN EN 61340-4-3:2002.

E-Mail info@rescue-tec.de +49-6482-608900

+49-6482-608920

• kompetent in der Beratung • zuverlässig in der Abwicklung

• **schnell** im Service

25.04.2024 2 von 2



HAIX Vario Wide Fit System

The width of the shoe can be individually adjusted by 3 different insoles. The shoe is supplied with a red insole (medium). A yellow insole (wide) and blue insole (narrow) can be ordered separately.

Sun Reflect

Reduces the heating effect of the upper leather by direct sunlight. Sunlight is reflected by the leather, keeping the leather and the feet cooler.

Others

Low weight, pulling strap

CE EN ISO 20345:2011 S3 HRO HI CI WR SRC

sizes: UK 4-12 / EU 37-47

E-Mail info@rescue-tec.de

Tel.: +49-6482-608900

Fax.: +49-6482-608920