

**NEW!**

# 3-Year 4-Gas Multi Gas Clip Simple Plus

Calibration not necessary and no charging ever

**This Year**

January	February
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28
March	April
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30
May	June
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30
July	August
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31
September	October
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31
November	December
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

**Next Year**



**Year After That**

January	February
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29
March	April
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30
May	June
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30
July	August
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31
September	October
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31
November	December
Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30	Su 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

- Operates for 3 years continuously with no charging
- Detects combustible gases (LEL), hydrogen sulfide (H<sub>2</sub>S), carbon monoxide (CO) & oxygen (O<sub>2</sub>)
- No calibration necessary - saves test gas & valuable time
- Infrared LEL sensor does not require oxygen to detect gas
- Low maintenance cost - infrared LEL sensor is immune to poisons
- Simple to use one button operation - large, easy to read screen
- Lightweight & durable - alligator clip clamps on tight



Portable gas detectors you can count on

gascliptech.com • +1.972.775.7577 • Toll-free: 1.877.525.0808  
email: info@gascliptech.com

## Multi Gas Clip Simple Plus Version

<b>Multi Gas Clip Simple Plus</b> Part# MGC-S-PLUS	Non-charging infrared three year four gas detector for H <sub>2</sub> S, CO, O <sub>2</sub> & LEL
---	---

Included with detector: calibration cap, calibration certificate & Quick Start Guide

## Multi Gas Clip Simple Plus Accessories



**Multi Gas Clip Simple Dock**  
 Part# MGC-S-DOCK\*  
 High pressure Part# MGC-S-DOCK-HP



**Multi Gas Clip Simple Wall Mount Dock**  
 Part# MGC-S-WMDOCK\*  
 High pressure Part# MGC-S-WMDOCK-HP



**MGC-S External Dust Filter Cap plus 5 Filters**  
 Part# MGC-S-XFILTER-KIT  
**Replacement Filters (Qty. 10)**  
 Part# MGC-S-XFILTER-10



**GCT IR Link**  
 Part# GCT-IR-LINK



**MGC Remote Sampling Probe**  
 Part# MGC-PROBE-1



**MGC-S Hand Aspirator Kit**  
 Part# MGC-S-HAK



**Quad Gas Cylinders**  
 25ppm H<sub>2</sub>S, 100ppm CO, 18% O<sub>2</sub> & 50% LEL  
 58L Part# MGC-Q-58  
 116L Part# MGC-Q-116






**MGC-S Confined Space Kit w/Gas Kit Without Gas**  
 Part# MGC-S-CSK-GAS\*  
 Part# MGC-S-CSK

\*Detector(s) not included

Please contact Gas Clip Technologies for additional spares, accessories and gas.

**Distributed by:**

## SPECIFICATIONS

<b>Size</b>	4.75" H x 2.75" W x 1.25" D (120.65 x 69.85 x 31.75 mm.)
<b>Weight</b>	7.675 oz. (220.2 g)
<b>Temperature</b>	-4° to +122°F (-20° to +50°C)
<b>Humidity</b>	5% to 95% RH (non-condensing)
<b>Battery Life</b>	1095 Days continuous (based on avg. of 1.5 min. of alarm/day)
<b>Alarms</b>	Visual, vibrating & audible (minimum 95 dB) Low, High, STEL, TWA & OL (Over Limit)
<b>LEDs</b>	4 Red alarm bar LEDs Yellow back-light (activated on button press) Red back-light (activated on alarm condition) Yellow maintenance notification LED
<b>Display</b>	High viewing angle alphanumeric Liquid Crystal Display (LCD)
<b>Logs</b>	25 Bump tests 25 Events 25 Calibrations Continuous 1 second data logging (typical capacity > 2 months)
<b>Tests</b>	Full function self-test upon activation Sensors, battery and circuitry tests run continuously
<b>Ingress Protection</b>	IP 68
<b>Certifications and Approvals</b>	 CAN/CSA C22.2 152 CSA 16.70084100 ANS/UL-913 and ANSI/ISA-S12.13 Intrinsically Safe/Secureite Intrinsic <b>CSA:</b> Class I, Division 1, Group A, B, C, and D Class I, Zone 0, AEx ia IIC T4 Ga UL 60079-0, UL60079-11   <b>IECEx:</b> IECEx CSA 16.0038 IEC 60079-0:2011 IEC 60079-11:2011 Ex ia IIC T4 Ga <b>ATEX:</b> Sira 16ATEX2288 CE II 1 G Ex ia IIC T4 Ga EN 60079-0:2012/A11:2013 EN 60079-11:2012
<b>Warranty</b>	Full 3 years
<b>Gases</b>	H <sub>2</sub> S.....0 - 100 PPM (0.1 ppm increments) CO.....0 - 500 PPM (1 ppm increments) Combustible (LEL) .....0 - 100% LEL (0.1% increments) O <sub>2</sub> .....0 - 30% vol. (0.1% increments)
<b>Sensor Type</b>	H <sub>2</sub> S, CO & O <sub>2</sub> .....Plug-in electrochemical cell Combustible (LEL) .....Soldered infrared (IR)

### Can Be Calibrated

## USER OPTIONS

Custom user message	TWA method
TWA/STEL intervals	Sensor enable/disable
Languages (6)	SAFE display
Latching alarms	Dock lock
Self-test lock	Calibration gas concentration
Bump test interval	Calibration interval
Low/High alarm	TWA/STEL alarm
Maintenance notification	% LEL or % CH <sub>4</sub> by-vo

