

BAD BOY 2.0

INSTRUCTIONS FOR USE
GUIDE INFORMATION FOR USE



BAD BOY 2.0

TEXTILE PROTECTIVE GLOVE FOR TECHNICAL ASSISTANCE WITH MAXIMUM CUT PROTECTION

- palm out of highly cut-resistant aramid, silicone-coated
- back of the hand out of Spantex®
- with additional lining layer in the gusset
- protectors as knuckle protection
- shirred padding in the area of the knuckles neoprene cuff
- with velcro closure and pull-on loop
- with carabiner

The protective gloves meet the requirements of the European PPE Regulation [EU] 2016/425 and protect against mechanical risks (abrasion, cut, tear, puncture resistance), which are covered in the standards on which the certification is based. No protection against the impact of large molten metals - category III.

The standards applied are EN 388:2016 (protective gloves for protection against mechanical risks) and EN ISO 21420:2020(protective gloves - general requirements).

DESCRIPTION

The BAD BOY 2.0 is a textile protective glove for technical assistance. The glove has the highest cut resistance and is characterized by its special wearing comfort and high tactility.

In addition, the glove is equipped with sewn-on protectors in the knuckle area, which protect the hands from punches and abrasion.

Gloves are in compliance with the essential health and safety requirements of the Regulation [EU] 2016/425.

APPLICATION

1. The gloves should be used according to its purpose.
2. Before every use, the gloves should be checked for possible damage.
3. Damaged gloves reduce the protective properties. The gloves should be kept clean.
4. Gloves that have become wet must not be dried by means of heating equipment.
5. Improper use of gloves can cause serious injuries or burns. In this case, the manufacturer assumes no responsibility.

As a user of the gloves, please observe the following instructions: The gloves are only a part of the protective equipment for use. They protect the hands against heat and fire. However, they must not come into contact with open flames. At the same time, the gloves protect against mechanical risks such as abrasion, cuts, tearing and punctures. In cases where there is a risk of getting caught in moving machine parts, gloves should not be worn.

TECHNICAL DATA

EN 388:2016+A1:2018



4X43FP

	REQUEST	RESULT
Abrasion resistance	3	4
Cut resistance	2	X
Tear resistance	3	4
Puncture resistance	3	3
Dexterity	1	4
TDM:Cut	B	F
Impact protection		P

1= lowest performance levels; 4 (5) = highest performance levels [A= lowest and F= highest performance levels linear cut resistance]; 0 = indicates that the glove falls below the minimum performance level for the given individual hazard. X = indicates that the glove has not been submitted to the test or the test method appears not to be suitable / applicable.

BAD BOY 2.0

INSTRUCTIONS FOR USE
GUIDE INFORMATION FOR USE



BAD BOY 2.0

TEXTILE PROTECTIVE GLOVE FOR TECHNICAL ASSISTANCE WITH MAXIMUM CUT PROTECTION

CERTIFICATION

Notified certification body for personal protective equipment: [PSA]:
MIRTA-KONTRDOL d.o.o. Javorinska 3, HR-10040 Zagreb - Dubrava, Croatia

Notified body 2474

Certificate-no. OZQ271-CPT003/19-A4

GLOVE SIZES

Available in sizes 5 - 13

STORAGE

Store in a ventilated room, preferably protected from light and dry

LIABILITY

We accept no liability for damage caused by the non-targeted use of the PPE or by any use that does not comply 100% with the instructions for use given below. Please contact the manufacturer for further information regarding care instructions, repair and safe disposal methods.

GENERAL INFORMATION

The results stated in the test report are based on laboratory tests carried out exclusively on unused gloves. Transferring the results to gloves after care treatment requires appropriate tests to be carried out. The glove offers protection against puncturing with pointed objects in the sense of DIN EN 388:2016, but there is no protection against pointed objects such as injection needles. The glove offers some protection against accidental contact with chemicals, but is not a protective glove against chemicals and micro organisms in the sense of DIN EN 374-1:2016 +A1:2018.

The gloves do not contain any substances known to cause allergies.

Mechanical level of performance refers to the palm of the glove. Gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer. Performance levels are only applicable to the whole product including all layers.

CHECK

An optical check for dirt and damage is essential. Damaged gloves must be discarded. The expiration time depends on the degree of wear, use and area of application. The clothing has a shelf life of at least 8 years from the date of manufacture. Non compliance with the notes/regulations listed in this manual and individual stress during use may reduce the durability of PPE. It is not known that performance levels according to EN 388:2016 change after up to 8 years of appropriate storage. The product complies with the applicable essential safety requirements of Regulation (EU) 2016/425.

This is a category III PPE, it is subject to periodic inspections according to module C2.

The EU type-examination certificate according to module B and module C2 is carried out by:
MIRTA-KONTRDOL d.o.o. Javorinska 3, HR-10040 Zagreb - Dubrava, Croatia Notified Body 2474.

SIZE MARKING

Label inside

EN - NORM

EN ISO 21420:2020+ EN 388:2016+A1:2018

PICTOGRAM

EN ISO 21420:2020

EN 388: 2016



4X43F P

CARE AND REPAIR



alternative up to 60°

according to washing expertise Lars Reuter (master textile cleaner, Hamburg)

DECLARATION OF CONFORMITY

You will receive on request.